




aseke® WINDLASS CHAINS

GRADE 40, CONTINUOUS HOT GALVANIZED FOR THICK ZINK LAYER, BUT ALSO VERY SMOOTH SURFACE. PRODUCED ON GERMAN 'WAFIOS', FULLY AUTOMATIC CUTTING, BENDING, WELDING AND CALIBRATION MACHINES. PRODUCT CERTIFIED TO EN-10204 3.1 (CHEMICAL AND MECHANICAL PROPERTIES). THICK, SMOOTH, BUT EVEN SURFACE OF ZINK THROUGH TECHNOLOGICAL INNOVATION; CONTINUOUS' HOT GALVANISATION.

DIN 766/ISO 4565 STANDARD, CALIBRATED

ITEM NO	t	l	b	CA		METERS PER BUNDLE
				KG/M	MBL	
942006	6 MM	18,5	20	0,82	1 800 KG	50
942007	7 MM	22	23	1,00	2 600 KG	50
942008	8 MM	24	27	1,43	4 100 KG	34/50/100
942010	10 MM DIN 766	28	34	2,35	7 200 KG	50/100
942011	10 MM ISO 4565	30	36	2,74	7 200 KG	50
942013	13 MM	36	44	4	13 000 KG	50/100
942016	16 MM	45	54	5,73	17 300 KG	50/100
942019	19 MM	53	64	8,01	24300 KG	100



NORWEGIAN STANDARD SHORT LINK, CALIBRATED

ITEM NO	t	l	b	CA		METERS PER BUNDLE
				KG/M	MBL	
922006	6,5 MM	24	23	0,88	2 400 KG	50

CALIBRATED WINCH CHAINS ARE ALSO STOCKED IN SEA WATER RESISTANT AISI 316 L AND AISI 316, AS LISTED IN CATALOG PAGE 10.

CHAIN CUTTER

ITEM NO	WIDTH CM	LENGTH CM	MAX DIA. CAPACITY
950030	16	90	13 MM DIA



STAINLESS; CALIBRATED WINCH CHAINS ARE LISTED ON CATALOGUE PAGE 10