




aseke® TRAWL CHAINS GRADE 80

PRODUCED ON GERMAN 'WAFIOS', FULLY AUTOMATIC CUTTING, BENDING AND WELDING MACHINES
CERTIFIED TO EN-10204 3.1 (CHEMICAL AND MECHANICAL PROPERTIES)


SHORT LINK DIN 766, BLACK ELECTROPHORETIC SURFACE FOR USE BOTH FOR TRAWLING AS FOR LIFTING

ITEM NO	t	l	b	CA KG/M	MBL kN	TEST LOAD kN	METERS PER DRUM
921006 NY	6 MM	18	20,7	0,80	45,2	28,3	650
921007 NY	7 MM	21,5	24,5	1,08	61,6	38,5	500
921008 NY	8 MM	24	27,5	1,38	80,4	50,3	400
921010 NY	10 MM	30	34,5	2,22	126	78,5	250
921013 NY	13 MM	39	45	3,75	212	133	150
921016	16 MM	48	55,5	8,00	322	201	90
921019	19 MM	57	64	11,20	454	284	75
921022	22 MM	66	73,5	15,00	608	380	50
921026	26 MM	78	89	21,20	849	531	35
921032	32 MM	96	112	23,00	1290	804	22



MID LINK, SELF COLORED SURFACE NOT FOR LIFTING

ITEM NO	t	l	b	CA KG/M	MBL kN	TEST LOAD kN	METERS PER DRUM
921110	10 MM	40	34	1,97	126	63	250
921111	11 MM	41	42	2,25	152	76	240
921113	13 MM	50	46	3,52	212	107	150
921116	16 MM	64	56	5,09	322	161	100
921119	19 MM	76	66	7,14	454	227	75
921122	22 MM	87	75	9,71	610	305	60
921126	26 MM	92	90	13,71	850	425	50*



* = in Pallet crates



LONG LINK (DIN 763/DIN 5685C), SELF COLOURED SURFACE NOT FOR LIFTING

ITEM NO	t	l	b	CA KG/M	MBL kN	TEST LOAD kN	METERS PER DRUM/PALLET
921309	9 MM	59	36	1,475	102	51	350/750
921310	10 MM	65	40	1,818	126	63	300
921311	11 MM	72	41	2,251	152	76	240/-
921313	13 MM	80	50	3,064	212	107	150/-
921316	16 MM	100	62	4,509	322	161	110/230
921319	19 MM	100	66	6,493	454	227	75/160
921322	22 MM	127	82	8,747	610	305	50/-
921326	26 MM	145	88	10,72	850	425	30/-
921328	28 MM	153	94	13,525	980	490	30/-
921330	30 MM	160	102	15,7	1130	565	25/-
921332	32 MM	171	108	17,809	1288	644	20/-

