

**GAFFEL KROKER GRADE 80**

PRODUSERT IHT EN 1677-4, GUL LAKKERT, SIKKERHETSFAKTOR 1:4
LEVERES MED SERTIFIKAT EN-10204 3.1 (KJEMISKE OG MEKANISKE VERDIER)

GAFFELKROK MED SIKKERHETS LEPPE EN 1677-2, TYPE EK-12

VARE-NR	KJETTING DIM	LASTE HØYDE	GAPÅPNING LEPPE	WLL TONN	CA KG/STK	ANTALL PER ESKE
903206	6 MM	76	26	1,12	0,32	20
903208	7+8 MM	85,5	29	2,0	0,52	15
903210	10 MM	104	39	3,15	1,05	10
903213	13 MM	128	47	5,3	2,00	5
903216	16 MM	150	55	8,00	3,70	4

**INNKORTNINGS KROK MED GAFFEL EN 1677-1, TYPE EK-86**

VARE-NR	KJETTING DIM	LASTE HØYDE	GAPÅPNING	WLL TONN	KG/STK	ANTALL PER ESKE
903908	7+8 MM	74	11	2,0	0,32	20
903910	10 MM	104	13	3,15	0,73	10

**BLÅLAKKERT CLEVIS TYPE C-KROK FOR LASTSIKRING, TYPE EK-71**

VARE-NR	KJETTING DIM	TOTAL HØYDE	GAPÅPNING	BL TONN	KG/STK	ANTALL PER ESKE
903709	9 MM	152	38	10	0,5	30
903711	11 MM	174	45	15	0,9	25
903713	13 MM	200	52	20	1,4	20

**SELVLUKKENDE GAFFEL-KROK EN 1677-3, TYPE EK-82/738**

VARE-NR	KJETTING DIM	LASTE HØYDE	GAPÅPNING LEPPE	WLL TONN	KG/STK	ANTALL PER ESKE
903608	7+8 MM	121	34	2,0	0,9	26
903610	10 MM	146	44	3,15	1,5	14
903613	13 MM	182	52	5,3	2,9	6
903616	16 MM	218	60	8,00	5,6	3

**GRAVEMASKIN KROK EN 1677-2, TYPE EK-19, SIKKERHETSFAKTOR 1:5**

VARE-NR	LASTE HØYDE	GAPÅPNING LEPPE	WLL TONN	KG/STK	ANTALL PER ESKE
903802	67	26,5	2	0,8	4
903803	73,5	30,5	3	1,2	4
903805	94	34	5	2,5	4
903808	94	34	8	3,3	2
903810	134,5	51	10	5,2	2



LØSE SIKKERHETS LEPPER/BOLT/FJÆR LAGERFØRES OG KAN LEVERES I POSE Å 3 STK MED VARENUMMER X FOR KR 30,-/STK NETTO

LÅSELEPPE OG FJÆR FOR GAFFEL KROKER

VARE-NR	DIM	STK PER PLASTPOSE	NOK PER STK	VARE-NR	STK PER PLASTPOSE
903206 X	6-8	10	116,00	903608 X	10
903208 X	7/8-8	10	119,00	903610 X	10
903210 X	10-8	10	123,00	903613 X	10
903213 X	13-8	10	130,00	903616 X	10
903216 X	16-8	10	140,00		