

**ØYE KROKER GRADE 80**

PRODUSERT IHT EN 1677-4, GUL LAKKERT, SIKKERHETSFAKTOR 1:4
LEVERES MED SERTIFIKAT EN-10204 3.1 (KJEMISKE OG MEKANISKE VERDIER)

ØYEKROK MED SIKKERHETS LEPPE EN 1677-2, TYPE EK-13

VARE-NR	KJETTING DIM	TOTAL HØYDE	GAPÅPNING LEPPE	WLL TONN	KG/STK	ANTALL PER ESKE
903306	6 MM	108	24	1,12	0,3	20
903308	7+8 MM	133	30	2,0	0,5	20
903310	10 MM	167	34	3,15	1,0	18
903313	13 MM	213	39	5,3	1,7	9
903316	16 MM	255	46	8	3,3	6
903320	20 MM	305	40	12,5	5,2	3

**INNKORTNINGS KROK MED ØYE EN 1677-1, TYPE EK-85**

VARE-NR	KJETTING DIM	TOTAL HØYDE	GAPÅPNING	WLL TONN	KG/STK	ANTALL PER ESKE
903408	7+8 MM	88,5	10,8	2,0	0,3	20
903410	10 MM	121,5	13,0	3,15	0,8	20
903413	13 MM	158	16,5	5,3	1,4	15
903416	16 MM	169	19,2	8	2,3	8
903420	20 MM	219	24	12,5	4,6	3
903422	22 MM	259	28,0	15	8,2	2
903426	26 MM	298	30	21,2	9,8	2

**SELVLUKKENDE ØYE-KROK EN 1677-3, TYPE EK-737**

VARE-NR	KJETTING DIM	TOTAL HØYDE	GAPÅPNING LEPPE	WLL TONN	KG/STK	ANTALL PER ESKE
903506	6 MM	140	28	1,12	0,5	20
903508	7+8 MM	172	34	2,0	0,8	26
903510	10 MM	214,5	44	3,15	1,5	14
903513	13 MM	268	52	5,3	3,2	6
903516	16 MM	330	60	8,00	6,1	3
903520	20 MM	357	81	12,5	7,6	2
903522	22 MM	417	82	15,00	13,4	2

**SELVLUKKENDE SVIVEL-KROK EN 1677-3, TYPE EK-83/755**

VARE-NR	KJETTING DIM	LASTE HØYDE	GAPÅPNING LEPPE	WLL TONN	KG/STK	ANTALL PER ESKE
904908	7+8 MM	210	34	2,0	1,1	10
904910	10 MM	247	44	3,15	2,0	10
904913	13 MM	302	52	5,3	4,0	6
904916	16 MM	383	60	8,00	7,3	3

**STØPERI KROKER, EK-116**

VARE-NR	DIM	WLL	MBL TONN	KG/STK	ANTALL PER ESKE
901008	7+8 MM	2	8	0,72	20
901010	10 MM	3,15	12,6	1,25	12
901013	13 MM	5,3	21,2	2,32	6
901016	16 MM	8	32	3,45	4

**REP.SETT, SIKKERHETS KROK M/LEPPE**

VARE-NR	STK PER PLASTPOSE	NOK PER STK
903306 X	10	116,00
903308 X	10	119,00
903310 X	10	123,00
903313 X	10	130,00
903316 X	10	140,00

REP.SETT FOR SELVLUKKENDE KROKER

VARE-NR	STK PER PLASTPOSE
903608 X	10
903610 X	10
903613 X	10
903616 X	10