

**DIVERSE G80 KOMPONENTER**

PRODUSERT IHT EN 1677-4, PVC COATED, SIKKERHETSFAKTOR 1:4
LEVERES MED SERTIFIKAT EN-10204 3.1 (KJEMISKE OG MEKANISKE VERDIER)

KUMRING BESLAG EK-101

VARE-NR	WLL	TOTAL HØYDE MM	GAPÅPNING LEPPE	MBL TONN	CA KG/STK	STK PER KARTONG
901205	1T - 1,3T	186	11,5	5,2	0,89	15
901210	1,5T - 2,5T	227	16	10	1,30	8
901221	3T - 5T	282	22	20	3,24	4
901240	6T - 10T	391	30	40	10,01	2
901280	12T - 20T	497	42	80	20,37	1

**SVEISBARE SURREFESTER**

VARE NR	EK TYPE	WLL	MBL TONN	CA KG/STK	STK PER KARTONG
904302	EK-344	5,3 T	21,2	1,46	15
904304	EK-310	9 T	36	2,75	6

**aseke[®] TROMMEL LØFTER MED KULELAGER SVIVEL**

VARE NR	FOR HULL DIA TROMMEL	KJETTING DIM	WLL TONN 1:4	MBL kN	CA KG/PC	STK PER KARTONG
921908	45 MM	8 MM	2	80,4	4,4	1
921910	65 MM	10 MM	3,15	126	6,7	1
921913	70 MM	13 MM	5,3	212	13,1	1

**aseke[®] FAT LØFTER**

VARE NR	TOTAL LENGDE	KJETTING DIA	WLL TONN 1:4	MBL TONN	CA KG/STK	STK PER KARTONG
921920	690 MM	6 MM	0,7	2,8	3,0	1

