



C-LÄNKAR

CERTIFIERADE ENLIGT EN 10204 - 3.1

VARMGALVANISERAT GRADE 60 STÅL (Produktgrupp 316 Komponenter)

| ART-NR | DIM | INNV. LÄNGD | INNV. BREDD | GAP ÖPPNING | CA | |
|--------|-------|----------------|----------------|----------------|------------------|-------------------|
| | | | | | BROTT- STYRKA | ANTAL PER FÖRP |
| 882010 | 10 MM | 50 MM | 16 MM | 2 MM | 1000 KG | 100 |
| 882012 | 12 MM | 55 MM | 18 MM | 2 MM | 2000 KG | 100 |
| 882016 | 16 MM | 72 MM | 21 MM | 2 MM | 3500 KG | 60 |
| 882020 | 19 MM | 80 MM | 24 MM | 2 MM | 7000 KG | 50 |
| 882022 | 22 MM | 88 MM | 27 MM | 3 MM | 9000 KG | 40 |
| 882025 | 25 MM | 94 MM | 35 MM | 3 MM | 10100 KG | 16 |

SYRAFAST, SJÖVATTENBESTÄNDIG AISI 316 (Produktgrupp 316 Komponenter)

| ART-NR | DIM | INNV. LÄNGD | INNV. BREDD | GAP ÖPPNING | CA | |
|--------|-------|----------------|----------------|----------------|------------------|-------------------|
| | | | | | BROTT- STYRKA | ANTAL PER FÖRP |
| 102822 | 8 MM | 46 MM | 14 MM | 1 MM | 650 KG | 50 |
| 102823 | 10 MM | 50 MM | 16 MM | 1,5 MM | 1000 KG | 50 |
| 102824 | 12 MM | 55 MM | 18 MM | 1,5 MM | 2000 KG | 50 |
| 102826 | 14 MM | 60 MM | 18 MM | 1,5 MM | 2500 KG | 50 |
| 102825 | 16 MM | 72 MM | 21 MM | 2 MM | 3500 KG | 50 |
| 102827 | 19 MM | 80 MM | 24 MM | 2 MM | 7000 KG | 20 |
| 102828 | 22 MM | 88 MM | 27 MM | 3 MM | 9000 KG | 20 |
| 102829 | 25 MM | 94 MM | 35 MM | 3 MM | 10100 KG | 10 |
| 102830 | 28 MM | 100 MM | 39 MM | 4 MM | 12000 KG | 6 |

