




LYFTÖGLA MED TAPP FÖR LYFT, DIN 580

SMIDDA I C15 STÅL, VARMGALVANISERADE, METRISKA GÄNGOR.

MÄRTKA MED: TILLVERKARENS ID, C€, WLL, DIM.

CERTIFIERADE ENLIGT EN 10204 3.1 (KEMISKA OCH MEKANISKA EGENSKAPER).

ART-NR	d	H	b	c	L	RAK BELASTNING	ANTAL
						WLL 1:4	PER FÖRP
103106	M 6	47	16	6	13	0,09T	100
103108	M 8	49	20	8	13	0,14T	100
103110	M 10	62	25	10	17	0,23T	100
103112	M 12	73	30	12	20,5	0,34T	100
103114	M 14	89	35	14	27	0,5T	50
103116	M 16	89	35	14	27	0,7T	50
103118	M 18	101	40	16	30	0,93T	30
103120	M 20	101	40	16	30	1,2T	30
103122	M 22	126	50	20	36	1,5T	30
103124	M 24	126	50	20	36	1,8T	20
103130	M 30	154	60	24	45	3,2T	10
103136	M 36	182	70	28	54	5,1T	5



LYFTÖGLA MED HÅL FÖR LYFT, DIN 582

ART-NR	d	H	b	c	L	RAK BELASTNING	ANTAL
						WLL 1:4	PER FÖRP
103206	M 6	34	20	6	0	0,09T	100
103208	M 8	36	20	8	0	0,14T	100
103210	M 10	45	25	10	0	0,23T	100
103212	M 12	53	30	12	0	0,34T	100
103214	M 14	62	35	14	0	0,5T	50
103216	M 16	62	35	14	0	0,7T	50
103220	M 20	71	40	16	0	1,2T	30
103224	M 24	90	50	20	0	1,8T	20
103230	M 30	109	60	24	0	3,2T	10
103236	M 36	128	70	28	0	5,1T	5

