

**aseke® OFFSHORE SHACKLES acc to DNV-GL 2.7-1**

TYPE EK-362A, THERMIC DIFFUSION SHERADIZED GALVANIZED SURFACE TREATMENT FOR EXTENDED LIFE-LENGTH. SAFETY FACTOR 1:6, MARKED: aseke, OFFS, ID-CODE, WLL, C€
 SUPPLIED WITH CERTIFICATE FORM 4, PRODUCT CERTIFICATE EN 10204-3.1, DOCUMENT OF CONFORMITY AND USER MANUAL. TYPE APPROVED ACC TO DNV-GL 2.7-1, 2.7-3 AND ISO 10885 BY DNV-GL CERTIFICATE NO TAS00002ND.

BOW SHACKLES WITH BROAD NUT AND LARGE SAFETY SPLIT PIN

ITEM NO	BOW X BOLT	W L L TONS	GAP OPENING	INNER HEIGHT	INNER WIDTH	PACK UNIT
902413	13 X 16 MM	2	20	47	33	50
902416	16 X 19 MM	3,25	27	60	42	25
902420	19 X 22 MM	4,75	31	71	51	15
902422	22 X 25 MM	6,5	36	84	58	12
902425	25 X 28 MM	8,5	42	95	68	8
902428	28 X 32 MM	9,5	46	108	74	6
902432	32 X 35 MM	12	51	119	82	4
902435	35 X 38 MM	13,5	57	131	89	3
902438	38 X 42 MM	17	60	148	98	2
902445	45 X 51 MM	25	73	177	127	2

HOT DIP GALVANIZED SPILT PINS FOR aseke LIFTING AND OFFSHORE SHACKLES

ITEM NO	FOR SHACKLE BOLT DIA	SHACKLE WLL	SUITABLE FOR HOLE DIA	PCS PER PLASTIC BAG	NOK PER PIECE
902816 X	16 + 19 MM	2 - 3,25	4,5	10	16,50
902822 X	22 - 35 MM	4,75 - 25	5,5	10	29,00

