



## aseke® OFFSHORE LIFTING SHACKLES acc to DNV 2.7-1/2.7-3 and NORSOK R-002

TYPE EK-2073, GRADE 80 AT MINUS 40 DEGREES, THERMIC DIFFUSION SHERADIZED GALVANIZED SURFACE TREATMENT FOR EXTENDED LIFE LENGTH. SAFETY FACTOR 1:6, MARKED: aseke, OFFS, ID-CODE, WLL, C€ SUPPLIED WITH CERTIFICATE FORM 4, PRODUCT CERTIFICATE ONIX, EN 10204-3.1, DOCUMENT OF CONFORMITY AND USER MANUAL. TYPE APPROVED ACC TO DNV-GL 2.7-1/2.7-3, NORSOK R-002/003 AND ISO 2415 BY DNV CERTIFICATE NO TAS00004XC.

### BOW SHACKLES WITH BROAD NUT AND LARGE SAFETY SPLIT PIN

ITEM NO	BOW X BOLT	W L L TONS	GAP OPENING	INNER HEIGHT	INNER WIDTH	PACK UNIT
902313	13 X 16 MM	2	20	47	33	30
902316	16 X 19 MM	3,25	27	60	42	25
902320	19 X 22 MM	4,75	31	71	51	15
902322	22 X 25 MM	6,5	36	84	58	12
902325	25 X 28 MM	8,5	42	95	68	8
902328	28 X 32 MM	9,5	46	108	74	6
902332	32 X 35 MM	12	51	119	82	4
902335	35 X 38 MM	13,5	57	131	89	3
902338	38 X 42 MM	17	60	148	98	2
902345	45 X 51 MM	25	73	177	127	2
902350	51 X 57 MM	35	82	197	146	1
902364	69 X 70 MM	55	105	267	179	1

### HOT DIP GALVANIZED SPILT PINS FOR aseke LIFTING AND OFFSHORE SHACKLES

ITEM NO	FOR SHACKLE BOLT DIA	SHACKLE WLL	SUITABLE FOR HOLE DIA	PCS PER PLASTIC BAG
902816X	16 + 19 MM	2 - 3,25	4,5	10
902822X	22 - 35 MM	4,75 - 25	5,5	10



**NOTE** We also possess DNV typeapproval for the same series Offshore lifting shackles in Grade 60 with type approval no TAS00002ND. We will send our type approval certificate upon inquiry.