



## aseke® LIFTING SHACKLES ACC TO NS-EN 13889

Thermic Diffusion Sheradized Galvanized Surface Treatment for Extended Lifetime without Rust.

Safety Factor 1:6 WLL 200T+250T = Safety Factor 1:4

Product certified to EN 10204-3.1, Marked: aseke, ID-CODE, WLL, CE

WLL 5St upwards are produced in Alloy 42CrMo for better properties as to aging and yield

### Bow Shackles with Broad Nut and Large Safety Split Pin

Item No	Bow x Bolt	W L L	GAP	INNER	INNER	PACK
		TONS	OPENING	HEIGHT	WIDTH	
902806	6 X 8 MM	0,50	13	26	19	100
902808	8 X 10 MM	0,75	13	26	21	100
902810	10 X 11 MM	1	16	35	26	100
902811	11 X 13 MM	1,5	19	42	29	150
902813	13 X 16 MM	2	20	47	33	100
902816	16 X 19 MM	3,25	27	60	42	50
902820	19 X 22 MM	4,75	31	71	51	30
902822	22 X 25 MM	6,5	36	84	58	20
902825	25 X 28 MM	8,5	42	95	68	15
902828	28 X 32 MM	9,5	46	108	74	10
902832	32 X 35 MM	12	51	119	82	8
902835	35 X 38 MM	13,5	57	131	89	8
902838	38 X 42 MM	17	60	148	98	5
902845	45 X 51 MM	25	73	177	127	2
902851	51 X 57 MM	35	82	197	146	2
902864	69 X 70 MM	55	105	267	179	1
902876	79 X 85 MM	85	127	327	200	1
902889	92 X 95 MM	120	133	372	229	1
902899	100 X 107 MM	150	140	368	254	1
902901	115 X 120 MM	200	184	398	279	1
902902	127 X 135 MM	250	216	506	330	1



### Bow Shackles with Threaded Eye Bolt

Item No	Bow x Bolt	W L L	GAP	INNER	INNER	PACK
		TONS	OPENING	HEIGHT	WIDTH	
902713	13 X 16 MM	2	0	47	33	50
902716	16 X 19 MM	3,25	27	60	42	50
902720	19 X 22 MM	4,75	31	71	51	40
902722	22 X 25 MM	6,5	36	84	58	20
902725	25 X 28 MM	8,5	42	95	68	15
902728	28 X 32 MM	9,5	46	108	74	10
902732	32 X 35 MM	12	51	119	82	10
902735	35 X 38 MM	13,5	57	131	89	8
902738	38 X 42 MM	17	60	148	98	4
902745	45 X 51 MM	25	73	177	127	2
902751	51 X 57 MM	35	82	197	146	2
902764	69 X 70 MM	55	105	267	179	1



### D Shackles with Threaded Eye Bolt

Item No	Bow x Bolt	W L L	GAP	INNER	PACK
		TONS	OPENING	HEIGHT	
902613	13 X 16 MM	2	20	41	50
902616	16 X 19 MM	3,25	27	51	50
902620	19 X 22 MM	4,75	31	60	40
902622	22 X 25 MM	6,5	36	71	20
902625	25 X 28 MM	8,5	42	81	15
902628	28 X 32 MM	9,5	46	91	10
902632	32 X 35 MM	12	51,5	100	10
902635	35 X 38 MM	13,5	57	111	8
902638	38 X 42 MM	17	60	124	5



### PVC COVERED COPPER WIRE (AS AN ALTERNATIVE TO THE STANDARD SPLIT PINS FOR BOLT SECURING)

Item No	OUTER DIA	WIRE	SUITABLE	PCS PER
	DIA	MATERIAL	FOR HOLE DIA	BAG
902903	5 MM	COPPER	ALL	10
902904	5 MM	ALUMINIUM	ALL	10



### HOT DIP GALVANIZED SPLIT PINS

Item No	FOR SHACKLE	SHACKLE	SUITABLE FOR	PCS PER
	BOLT DIA	WLL	HOLE DIA	BAG
902813 X	13 MM	1,50	4,2	10
902816 X	16 + 19 MM	2 - 3,25	4,5	10
902822 X	22 - 35 MM	4,75 - 25	5,5	10

