



aseke® SHACKLES WITH COUNTERSUNK HEAD PIN

TYPE D GRADE 60, HOT DIP GALVANIZED WITH BOLT WITH A SQUARE HOLE FOR USE WITH A SQUARE BIT KEY. THE BOLT IS ADDITIONALLY POWDER COATED. CERTIFIED TO EN10204-3.1

ITEM NO	BOW X BOLT	WLL 1:6 TONS	GAP OPENING	INNER HEIGHT	AQUARE BIT KEY	PACK UNIT
902208	08 X 10 MM	0,75	13,5	26,5	5 X 5 MM	100
902210	10 X 11 MM	1,00	17	32	5 X 5 MM	100
902213	13 X 16 MM	2,00	22,0	43,0	10 X 10 MM	60
902216	16 X 19 MM	3,25	27	51	10 X 10 MM	40
902220	19 X 22 MM	4,75	31,0	59,0	10 X 10 MM	20
902222	22 X 25 MM	6,50	36	73	12 X 12 MM	15
902225	25 X 28 MM	8,50	43,0	85,5	12 X 12 MM	10



BIT-KEYS FOR SHACKLE BOLT WITH COUNTERSUNK SQUARE HOLE

ITEM NO	SIZE KEY	FOR DIA SHACKLE BOLT	LENGTH	NO PER PASTIC BAG
902700	5 X 5 MM STRAIGHT	8+10 MM	60 MM	10
902704	5 X 5 MM L-TYPE	8+10 MM	110 MM	10
902699	10 X 10 MM STRAIGHT	13+16+19 MM	60 MM	10
902701	10 X 10 MM L-TYPE	13+16+19 MM	110 MM	10
902702	12 X 12 MM L-TYPE	22+25 MM	110 MM	6
902703	14 X 14 MM L-TYPE	32 MM	110 MM	6

HOT DIP GALV D-SHACKLE FOR SCREWDRIVER SAME DIAMETER BOLT AND BOW

ITEM NO	BOLT X BOW	GAP OPENING	INNER HEIGHT	INNER WIDTH	PACK UNIT
901109	10 x 10 MM	19 MM	37 MM	19 MM	100

