



THIMBLES for fiberropes and hawsers

CERTIFIED TO CHEMICAL PROPERTIES.

THE K-3 TYPE AND THE TUBULAR THIMBLES ARE PRODUCT CERTIFIED TO NS 9415:2009 BY CERTIFICATE NO PSB011.

ELECTROLYTICALLY GALVANIZED THIMBLE DIN 6899, TYPE B

ITEM NO	for ROPE DIA	TOTAL LENGTH	I	c	MATERIAL THICKNESS	KG/PIECE	MBL TONS	PACK UNIT
905006	5+6 MM	1 3/4"	28 MM	18 MM	2,2 MM	0,030	-	500
905010	8-10 MM	2 1/2"	38 MM	23 MM	2,5 MM	0,050	-	250



CASTED, HOT DIP GALVANIZED (CA 70 MICRON) HAWSER THIMBLE TYPE K-3

PRODUCT CERTIFIED TO NS 9415:2009 BY CERTIFICATE NO PSB011.

ITEM NO	FOR ROPE/ HAWSER DIA	TOTAL LENGTH	INNER HEIGHT	INNER WIDTH	MATERIAL THICKNESS	KG/PIECE	MBL TONS	PACK UNIT
905220	18-20 MM	3"=77	58 MM	38 MM	3 MM	0,19	6,60	50
905225	21-26 MM	3 1/2"=91	74 MM	42 MM	4 MM	0,28	10	50
905232	27-32 MM	4"=102	78 MM	50 MM	5 MM	0,42	20	50
905240	34-40 MM	5"=127	100 MM	65 MM	6 MM	0,78	32	40
905248	41-49 MM	6"=152	130 MM	75 MM	7 MM	1,30	47	20
905256	50-60 MM	7"=178	142 MM	85 MM	7,5 MM	1,80	64	15
905264	61-65 MM	8"=203	170 MM	105 MM	8 MM	3,20	93	8
905272	66-72 MM	9"=230	185 MM	110 MM	10 MM	5,00	113	6
905280	73-82 MM	10"=254	200 MM	120 MM	10 MM	6,10	138	4
905290	83-90 MM	11"=280	210 MM	145 MM	12 MM	10,30	185	2
905300	91-102 MM	12"=305	230 MM	150 MM	12 MM	15,00	237,5	1
905315	103-115 MM	14"=355	290 MM	170 MM	14 MM	18,30	257	1



HOT DIP GALVANIZED (CA 70 MICRON) TUBULAR THIMBLE, POINTED TYPE

PRODUCT CERTIFIED TO NS 9415:2009 BY CERTIFICATE NO PSB011.

ITEM NO	FOR ROPE/ HAWSER DIA	TOTAL LENGTH	REEL HEIGHT	INNER WIDTH	MATERIAL THICKNESS	KG/PIECE	MBL TONS	PACK UNIT
905320	18-20 MM	7"=180	25 MM	45 MM	6 MM	1,40	8,5	20
905324	21-24 MM	7 1/2"=195	30 MM	47 MM	7 MM	2,00	12,5	15
905328	25-28 MM	8 1/2"=215	35 MM	60 MM	7 MM	2,40	15	10
905332	29-32 MM	9 1/2"=240	40 MM	65 MM	7 MM	3,10	25,2	8
905336	33-36 MM	11"=280	50 MM	75 MM	7 MM	4,06	35	7
905340	37-40 MM	11 1/2"=298	55 MM	85 MM	7 MM	5,95	44	5
905344	41-44 MM	12"=308	60 MM	86 MM	7 MM	6,85	50	4
905348	45-48 MM	12 1/2"=312	65 MM	88 MM	7 MM	7,20	58,0	3
905356	49-56 MM	13"=332	70 MM	90 MM	7 MM	7,60	80	2
905364	57-64 MM	13 1/2"=342	75 MM	94 MM	7 MM	8,30	116,2	2
905372	65-72 MM	17 1/2"=450	88 MM	130 MM	10 MM	20,11	141,2	1
905380	73-80 MM	19 1/2"=500	94 MM	150 MM	10 MM	24,85	172,5	1
905392	81-92 MM	21 1/2"=550	107 MM	190 MM	10 MM	30,43	230,0	1
905396	96 MM	24"=600	112 MM	200 MM	14 MM	50,40	250	1
905400	104 MM	26"=650	120 MM	220 MM	16 MM	68,80	295	1
905401	115 MM	30"=750	140 MM	240 MM	20 MM	110,0	320	1

