

**GRADE 100 KOMPONENTER**

PRODUSERT IHT EN 1677-4, BLÅ PULVER LAKKERT RAL 5015, SIKKERHETSFAKTOR 1:4
LEVERES MED SERTIFIKAT EN-10204 3.1 (KJEMISKE OG MEKANISKE VERDIER)

aseke KOPLINGS LEDD TYPE EK-1001, EN 1677-1

VARE-NR	KJETTING DIM	WLL TONN	TOTAL HØYDE	LYS- ÅPNING	ANLEGG- DIA	CA KG/STK	ANTALL PER ESKE
984606	6 MM	1,4	44,5	14	7,0	0,11	20
984608	8 MM	2,5	61,5	18,5	10	0,18	20
984610	10 MM	4	72	23	12,6	0,34	20
984613	13 MM	6,7	92	28	16,5	0,68	20
984616	16 MM	10	107	33,5	20	1,22	20

**GAFFELKROK MED SIKKERHETS LEPPE TYPE EK-1004, EN 1677-2**

VARE-NR	KJETTING DIM	WLL TONN	TOTAL HØYDE	GAP ÅPNING LEPPE	CA KG/STK	ANTALL PER ESKE
983206	6 MM	1,4	109	18,5	0,33	20
983208	8 MM	2,5	134	25	0,7	15
983210	10 MM	4	161,5	28	1,3	15
983213	13 MM	6,7	203	38	2,3	5
983216	16 MM	10	248	44	3,6	4

**SELVLUKKENDE GAFFEL KROK TYPE EK-1006, EN 1677-3**

VARE-NR	KJETTING DIM	WLL TONN	TOTAL HØYDE	GAP ÅPNING LEPPE	CA KG/STK	ANTALL PER ESKE
983606	6 MM	1,4	131	28	0,5	25
983608	8 MM	2,5	166	35,5	0,9	25
983610	10 MM	4	196,5	45	1,6	14
983613	13 MM	6,7	251	53,5	2,9	6
983616	16 MM	10	303	62	5,8	3

**SELVLUKKENDE KROK MED ØYE TYPE EK-1005, EN 1677-3**

VARE-NR	KJETTING DIM	WLL TONN	TOTAL HØYDE	GAP ÅPNING LEPPE	CA KG/STK	ANTALL PER ESKE
983506	6 MM	1,4	141	28	0,5	20
983508	8 MM	2,5	175	36	0,9	25
983510	10 MM	4	212	45	1,5	14
983513	13 MM	6,7	269	53	2,7	6
983516	16 MM	10	333	61	5,7	3
983520	20 MM	16	368	76	7,9	2
983522	22 MM	10	417	76	11,2	2

**INNKORTNINGS ØYE KROK TYPE EK-1008, EN 1677-1,**

VARE-NR	KJETTING DIM	WLL TONN	TOTAL HØYDE	GAPÅPNING	CA KG/STK	ANTALL PER ESKE
983406	6 MM	1,4	71	8	0,2	20
983408	8 MM	2,5	93	11	0,34	20
983410	10 MM	4	128	13,5	0,82	10
983413	13 MM	7	163	16,5	1,6	10
983416	16 MM	10	183	19,2	2,45	10

**TOPPLØKKER/MASTER LINK TYPE EK-1013, EN 1677-4**

VARE-NR	KJETTING DIM	WLL T	GODS DIA MM	INNVEDIG HØYDE	BREDDE	KG/STK	ANTALL PER ESKE
984334	2016-10	17	32	240	140	5,1	4
984342	2220-10	25	38	250	150	7,2	2

TOPPLØKKER EN 1677-4, TYPE EK-95

VARE-NR	KJETTING DIM	WLL T	GODS DIA MM	INNVEDIG HØYDE	BREDDE	KG/STK	ANTALL PER ESKE
905813	76-8	2,7	13	115	60	0,35	20
905816	87+8-8	4,1	16	120	70	0,60	20
905820	10-8	6,7	20	150	80	1,10	15
905822	1310-8	8,2	22	170	90	1,53	10
905825	1613-8	10,7	25	190	100	2,21	6
905828	1816-8	12,9	28	210	110	3,06	4
905832	19-8	17,1	32	270	140	5,05	3
905838	2018-8	28,1	38	270	140	7,30	2
905845	2220-8	38,3	45	320	170	12,20	2
905850	2622-8	45	50	380	200	17,65	2
905860	32-8	65,3	60	430	220	28,85	1
905870	36-8	84,4	70	500	250	45,48	1



LØFTEHODER, STOR TYPE EK-1015, EN 1677-4

VARE-NR	KJETTING		TOPP LØKKE MM		BALANSE LØKKER MM	KG/STK	ANTALL PER ESKE
	DIM	WLL T					
987519	6-10	3,5	150	60	120 X 70	1,8	10
987522	8-10	5,3	160	95	140 X 80	3,0	8
987540	13-10	17	250	150	190 X 110	15	2
987550	16-10	28	300	200	200 X 120	23	1

LØFTEHODER, STOR TYPE EN 1677-4, TYPE EK-96

VARE-NR	KJETTING		TOPP LØKKE		BALANSE LØKKER	KG/STK	ANTALL PER ESKE
	DIM	WLL T					
905916	6-8	4,1	120	70	95 x 51	1,19	10
905920	7-8	6,5	170	90	120 x 70	2,5	6
905922	8-8	8,2	170	90	150 x 80	3,77	5
905925	9-8	10,7	190	100	150 x 80	4,45	4
905928	10-8	12,9	210	110	170 x 90	6,12	2
905932	13-8	17,1	270	140	190 x 100	9,47	2
905938	16-8	28,1	270	140	270 x 140	17,4	1
905945	20-8	38,3	320	170	270 x 140	26,7	1
905950	22-8	45	380	200	270 x 140	33,2	1
905960	26-8	65,8	430	220	380 x 200	65	1
905970	32-8	84,4	500	250	430 x 220	103	1



RUNDSLING KROKER EK-1055 IHT EN 1677

VARE NR	WLL	FARGE	KG/STK	PAKKENHET	
				STK	
983701	1 T	LILLA	0,73	10	
983702	2 T	GRØNN	1,28	10	
983703	3 T	GUL	2,23	8	
983705	5 T	RØD	4,63	4	



REP.SETT MED LÅSELEPPE OG FJÆR FOR GAFFEL KROKER

VARE-NR	DIM	STK PER PLASTPOSE
903206 XNY	6-8	10
903208 XNY	7/8-8	10
903210 XNY	10-8	10
903213 XNY	13-8	10
903216 XNY	16-8	10



REP.SETT FOR SELVLUKKENDE KROKER

VARE-NR	STK PER POSE
983608 X	10
983610 X	10
983613 X	10
983616 X	10



LØSE KOBLINGSBOLTER MED LÅSEHYLSE TIL EK-74

VARE-NR	DIM	KG PER POSE	STK PER PLASTPOSE
904608 X	7/8-8	0,12	10
904610 X	10-8	0,25	10
904613 X	13-8	0,51	10
904616 X	16-8	0,89	10
904620 X	20-8	1,59	10
904622 X	22-8	2,43	10
904626 X	26-8	4,08	10
904632 X	32-8	7,30	10



LØSE KOBLINGSBOLTER MED LÅSESPLINT TIL EK-2 OMEGA KOPLING

VARE-NR	DIM	KG PER POSE	STK PER PLASTPOSE
904808 X	7/8-8	0,07	6
904810 X	10-8	0,20	6
904813 X	13-8	0,26	4
904816 X	16-8	0,50	4



NØYTRALE 10-KANTET ALU.ID-MERKESKILT FOR GRADE 100 FOR SERTIFISERTE KJETTING LØFTE REDSKAPER

VARE NR	TYPE	ANTALL PER POSE
M 16	EN-PART	10
M 17	FLER-PART	10
M 3	LÅSE WIRE	10

