



KOBLINGS LEDD / P-LEDD


USERTIFISERTE

NORMAL TYPE "QUICK LINK" KOBLINGSLEDD, ELEKTRO.GALVANISERT

VARE-NR	DIA				m	CA	ANTALL
	d1	GJENGER	d2	d3		BRUDDLAST	PER ESKE
881005	5 MM	7 MM	39,5 MM	13,5 MM	6,5 MM	700 KG	100
881006	6 MM	8 MM	45 MM	13,5 MM	7 MM	900 KG	100
881008	8 MM	10 MM	57,5 MM	18 MM	10 MM	1700 KG	50
881010	10 MM	12 MM	69 MM	20,5 MM	12 MM	2500 KG	50
881012	12 MM	14 MM	82,5 MM	23 MM	13,5 MM	2800 KG	20
881014	14 MM	17 MM	97 MM	26,5 MM	15 MM	3100 KG	10
881016	16 MM	19 MM	115 MM	29,5 MM	18 MM	5500 KG	10

LANG TYPE "QUICK LINK"/P-LEDD, ELEKTRO.GALVANISERT

VARE-NR	DIA				m	CA	ANTALL
	d1	GJENGER	d2	d3		BRUDDLAST	PER ESKE
881108	8 MM	11 MM	73 MM	19 MM	17,5 MM	1700 KG	100
881110	10 MM	13 MM	88 MM	22 MM	20,5 MM	2500 KG	100
881112	12 MM	15 MM	102 MM	25 MM	23,5 MM	2800 KG	100
881114	14 MM	18 MM	114 MM	28 MM	26,5 MM	3100 KG	50
881116	16 MM	19 MM	129 MM	31 MM	29,5 MM	7000 KG	30



HURTIGKOBLING, ELEKTRO.GALVANISERT

VARE-NR	DIM	CA	CA	CA	ANTALL
		INNVEDIG	INNVEDIG	GAP-ÅPNING	
880005	5 MM	23 MM	9,5 MM	5,5 MM	100
880006	6 MM	29 MM	10,5 MM	7 MM	100
880008	8 MM	37 MM	15 MM	9 MM	100
880010	10 MM	37,5 MM	17 MM	10 MM	100



ANDRE DIMENSJONER KAN PRODUSERES PÅ FORESPØRSEL.

S-KROKER, ELEKTRO.GALVANISERT

VARE NR	DIM	CA			ANTALL
		A	C	B	
880050	5 MM	50 MM	8 MM	15 MM	100
880060	6 MM	48 MM	9 MM	17,5 MM	100
880100	10 MM	80 MM	13,5 MM	30 MM	100

