



KOBLINGS LEDD / P-LEDD


USERTIFISERTE

NORMAL TYPE "QUICK LINK" KOBLINGSLEDD, ELEKTRO.GALVANISERT

VARE-NR	d1	DIA		d3	m	CA BRUDDLAST	ANTALL PER ESKE
		GJENGER	d2				
881005	5 MM	7 MM	39,5 MM	13,5 MM	6,5 MM	700 KG	100
881006	6 MM	8 MM	45 MM	13,5 MM	7 MM	900 KG	100
881008	8 MM	10 MM	57,5 MM	18 MM	10 MM	1700 KG	50
881010	10 MM	12 MM	69 MM	20,5 MM	12 MM	2500 KG	50
881012	12 MM	14 MM	82,5 MM	23 MM	13,5 MM	2800 KG	20
881014	14 MM	17 MM	97 MM	26,5 MM	15 MM	3100 KG	10
881016	16 MM	19 MM	115 MM	29,5 MM	18 MM	5500 KG	10

LANG TYPE "QUICK LINK"/P-LEDD, ELEKTRO.GALVANISERT

VARE-NR	d1	DIA		d3	m	CA BRUDDLAST	ANTALL PER ESKE
		GJENGER	d2				
881108	8 MM	11 MM	73 MM	19 MM	17,5 MM	1700 KG	100
881110	10 MM	13 MM	88 MM	22 MM	20,5 MM	2500 KG	100
881112	12 MM	15 MM	102 MM	25 MM	23,5 MM	2800 KG	100
881114	14 MM	18 MM	114 MM	28 MM	26,5 MM	3100 KG	50
881116	16 MM	19 MM	129 MM	31 MM	29,5 MM	7000 KG	30



SMETTELØKKER/C-LEDD/FLATLØKKER/PAR-LØKKER

VARMGALVANISERT GRADE 60 STÅL

VARE NR	DIM	INN- LENGDE	INN- BREDDE	GAP ÅPNING	CA BRUDD- STYRKE	ANTALL PER ESKE
882012	12 MM	55 MM	18 MM	2 MM	2000 KG	100
882014	14 MM	60 MM	18 MM	2 MM	3000 KG	80
882016	16 MM	72 MM	21 MM	2 MM	3500 KG	60
882020	19 MM	80 MM	24 MM	2 MM	7000 KG	50
882022	22 MM	88 MM	27 MM	3 MM	9000 KG	40
882025	25 MM	94 MM	35 MM	3 MM	10100 KG	16



HURTIGKOBLING, ELEKTRO.GALVANISERT

VARE-NR	DIM	CA	CA	CA	ANTALL PER ESKE
		INN- LENGDE	INN- BREDDE	GAP- ÅPNING	
880005	5 MM	23 MM	9,5 MM	5,5 MM	100
880006	6 MM	29 MM	10,5 MM	7 MM	100
880008	8 MM	37 MM	15 MM	9 MM	100
880010	10 MM	37,5 MM	17 MM	10 MM	100



S-KROKER, ELEKTRO.GALVANISERT

VARE NR	DIM	CA			ANTALL PER ESKE
		A	C	B	
880060	6 MM	48 MM	9 MM	17,5 MM	100
880100	10 MM	80 MM	13,5 MM	30 MM	100

