




## ØYEBOLT FOR LØFT, DIN 580

MERKET: PRODUSENTS LOGO, C€, WLL, DIM.

LEVERES MED SERTIFIKAT EN-10204 3.1 (KJEMISKE OG MEKANISKE VERDIER)

### VARMGALVANISERTE, C15 SMIDD STÅL, METRISKE GJENGER


VARE-NR	d	H	b	c	L = LENGDE	RETT STREKK	ESKE
					GJENGING	WLL 1:4	ENHET
103106	M 6	39	16	6	11	0,09T	100
103108	M 8	46	20	8	13	0,14T	100
103110	M 10	65	25	10	17	0,23T	100
103112	M 12	71	30	12	20,5	0,34T	100
103114	M 14	89	35	14	27	0,5T	50
103116	M 16	87	35	14	27	0,7T	50
103118	M 18	99	40	16	30	0,93T	30
103120	M 20	99	40	16	30	1,2T	30
103122	M 22	126	50	20	36	1,5T	30
103124	M 24	123	50	20	36	1,8T	20
103130	M 30	150	60	24	45	3,2T	10
103136	M 36	177	70	28	54	5,1T	5



## ØYEMUTTER FOR LØFT, DIN 582

### VARMGALVANISERTE, C15 SMIDD STÅL, METRISKE GJENGER


VARE-NR	d	H	b	c	RETT STREKK	ESKE
					WLL 1:4	ENHET
103206	M 6	28	16	6	0,09T	100
103208	M 8	33	20	8	0,14T	100
103210	M 10	42	25	10	0,23T	100
103212	M 12	51	30	12	0,34T	100
103214	M 14	60	35	14	0,5T	50
103216	M 16	60	35	14	0,7T	50
103220	M 20	69	40	16	1,2T	30
103224	M 24	87	50	20	1,8T	20
103230	M 30	105	60	24	3,2T	10
103236	M 36	123	70	28	5,1T	5



## ØYEBOLT FOR LØFT, DIN 580 SYREFAST

### SYREFAST, AISI 316 SMIDD STÅL, METRISKE GJENGER

VARE-NR	d	H	b	c	L = LENGDE	RETT STREKK	PAKK
					GJENGING	WLL 1:4	ENHET
103306	M 6	39	16	6	11	0,07T	25
103308	M 8	46	20	8	13	0,14T	25
103310	M 10	65	25	10	17	0,23T	25
103312	M 12	71	30	12	20,5	0,34T	25
103316	M 16	87	35	14	27	0,7T	10
103320	M 20	99	40	16	30	1,2T	10
103324	M 24	99	40	16	30	1,8T	5
103330	M 30	150	60	24	45	3,2T	5



**ØYEMUTTER FOR LØFT, DIN 582 SYREFAST  
SYREFAST, AISI 316 SMIDD STÅL, METRISKE GJENGER**

VARE-NR	d	H	b	c	RETT STREKK	PAKK
					WLL 1:4	ENHET
103406	M 6	28	16	6	0,07T	25
103408	M 8	33	20	8	0,14T	25
103410	M 10	42	25	10	0,23T	25
103412	M 12	51	30	12	0,34T	25
103416	M 16	60	35	14	0,7T	10
103420	M 20	69	40	16	1,2T	10
103424	M 24	87	50	20	1,8T	5
103430	M 30	105	60	24	3,2T	5

