



MORINGS TAU

Super Danline

UV STABILISERT SPESIALTAUVERK FOR FORTØYNINGER
PRODUSERT IHT. EN-NS 699 OG EN-NS ISO 1346
PRODUKT SERTIFISERT TIL NS 9415:2009 VED SERTIFIKAT NR PSB011.
TESTET IHT ISO 2307

3-SLATT TAU

CA 70% POLYPROPYLENE/30% POLYETYLENE, EGENVEKT 0,91, FORLENGELSE MAX 16%,
SMELTEPUNKT 165°C

VARE-NR	TAU DIA	KG PER METER	KG PER 110 m	MBL kP	KVEIL METER
918016	16 MM	0,118	12,8	4 550	110
918018	18 MM	0,148	16,3	5 550	110
918020	20 MM	0,182	19,8	6 650	110
918022	22 MM	0,22	24,2	8 100	110
918024	24 MM	0,259	28,6	9 300	110/220
918028	28 MM	0,357	39,1	13 200	110/220
918032	32 MM	0,46	50,6	16 800	110/220
918036	36 MM	0,585	64,5	20 600	110/220
918040	40 MM	0,72	79,2	25 700	110/220
918044	44 MM	0,88	96,8	30 170	110/220
918048	48 MM	1,04	114,5	36 600	110/220
918056	56 MM	1,42	156	52 000	110/220
918064	64 MM	1,85	203,5	64 100	110/220
918072	72 MM	2,34	257,5	84 500	110/220
918080	80 MM	2,90	319	104 000	110/220
918088	88 MM	3,51	386	125 000	110/220



8 PARTS FLETTET TROSSE

VARE-NR	TROSSE DIA	KG PER METER	KG PER 110 M	MBL KG	KVEIL METER
918132	32 MM	0,46	50,5	16 800	110
918136	36 MM	0,59	64,5	20 600	110
918140	40 MM	0,73	79,5	25 700	110
918148	48 MM	1,04	114,2	36 600	110
918156	56 MM	1,42	156	52 000	110
918160	60 MM	1,60	176	59 500	110
918164	64 MM	1,85	203,5	67 550	110
918172	72 MM	2,34	258	84 500	110
918180	80 MM	2,90	319	104 000	110
918188	88 MM	3,52	388	125 000	110



STROPPER MED KAUSE INNSPLEISET I EN ELLER BEGGE ENDER KAN PRODUSERES PÅ ORDRE